



**Baron-Blakeslee**  
A Wholly Owned Subsidiary of Service Filtration Corporation

Baron-Blakeslee SFC, Inc. 2900 MacArthur Boulevard, Northbrook, IL 60062-2005  
Sales: 855-793-5173, Corporate: 847-509-2910, Fax: 847-509-2908  
[www.baronblakeslee.com](http://www.baronblakeslee.com)

**Features & Benefits:**

- Small Footprint (Only 21" High)
- Operates On 120 VAC, Single Phase
- True Vapor Degreaser With Built In Solvent Distillation
  - Refrigerated Cooling Coils
- Wide Range Of Solvent Choices With BP 100°F-195°F
  - Low Emission Design To Conserve Solvent
  - Stainless Steel Basket Included
  - Electropolished Tanks
  - Stainless Steel Cabinet
- Offset Boil Tank To Prevent Dipping Parts In Dirty Solvent
  - Digital Boil Tank Temperature Display
- Sliding Cover (Available Powered Cover)
  - Increased Capacity Water Separator
  - Available Manual Spray Wand
  - Recirculating Filtration System
- Single (LK 612) Or Dual (LK 612-3) Immersion Models
  - Available Side Mounted Ultrasonics
  - Available Material Handling
  - Individual Tank Drains
- Low Solvent Level Safety Control
- High Vapor Level Safety Control
- Made In USA



**LAB KLEEN DESCRIPTION:**

The Lab Kleen is a tabletop precision vapor degreaser. This is a complete cleaning system consisting of electrical heating, refrigerated cooling, and all necessary safety controls.



**Baron-Blakeslee**  
A Wholly Owned Subsidiary of Service Filtration Corporation

**lab | kleen**

**LAB-KLEEN TABLETOP VAPOR DEGREASERS ARE AVAILABLE AS SINGLE (LK 612) OR DUAL (LK 612-3) IMMERSION MODELS**



Feature	Lab Kleen 612	Lab Kleen 612-3
Overall Dimensions	25" L-R, 27" F-B, 21" H	34 1/2" L-R, 26" F-B, 21" H
Weight	175 Pounds	180 Pounds
Working Tank Dimensions	12" L-R, 6" F-B, 5" Liquid Depth	12" L-R, 6" F-B, 5" Liquid Depth (each tank)
Boil Tank Dimensions	12" L-R, 6 1/2" F-B, and 5" Liquid Depth	12" L-R, 6 1/2" F-B, 5" Liquid Depth
Solvent Capacity	3.5 Gallons Total	5 Gallons Total
Boiling Range	100°F-195°F (non-flammable, approved vapor degreasing solvents only)	
Electrical	120 VAC/ 1 ph, 15 Amps, F.L.A.	
Heating	600 Watts (Bottom mounted. Override safety mounted inside offset boil tank)	
Refrigeration	1/4 HP,R-134a (EPA Approved Refrigerant)	
Circulation Pump/Filter	Pump is 1/20 HP, Filter is 2 1/2" diameter X 3 7/8" High	



Baron-Blakeslee SFC, Inc. 2900 MacArthur Boulevard, Northbrook, IL 60062-2005  
Sales: 855-793-5173, Corporate: 847-509-2910, Fax: 847-509-2908. [www.baronblakeslee.com](http://www.baronblakeslee.com)

ALL SPECIFICATIONS APPROXIMATE AND SUBJECT TO CHANGE WITHOUT NOTICE. BBLK0611rev1