



Baron Blakeslee

nanoskill



- Reduces Operating Costs
- Minimizes Solvent Waste & Environmental Impact
- Facilitates Maintenance
- Maximizes Production
- Cleaner Parts From Your Vapor Degreaser
- For Use With Small To Medium Size Vapor Degreasers
- Automatic, Continuous Distillation
- Built In Water Separator
- Easy To Clean Distillation Vessel
- Compact Form: 27" L X 24" W X 48" H
- For Use Only With Nonflammable Halogenated Hydrocarbon Vapor Degreasing Solvents Boiling Between 90°F - 160°F



Standard Features:

- Made In USA! 🇺🇸
- Allen-Bradley® PLC Control + Color Touchscreen HMI
- Programmable Automatic Start / Stop
- Refrigerated Condensing System (R-513A)
- 304 Stainless Steel Construction Of All Wetted Surfaces
- 304 Stainless Steel Skins
- Stainless Steel Ball Valve Drains
- Full Tank Insulation
- Self Priming Magnetic Drive Transfer Pump
- Gravity Type Internal Water Separator
- SCR Controlled Indirect Contact Electric Heater
- Thermocouple For Temperature Monitoring + Boil Down Control
- Completely Sealed Distillation Vessel
- Stainless Steel Flex Hoses For Connection To Vapor Degreaser
- Solvent Vapor Control
- Liquid Temperature Control
- Vibronic Type Level Controls
- User Selectable Control Settings For Multi-Solvent Capability
- Structural Frame With Locking Casters
- 24 VDC Control Voltage
- One Year Limited Warranty



Technical Specifications:

- | | |
|--|--------------------------------|
| • Overall Dimensions: | 27" Long x 24" Wide x 48" High |
| • Heat Input: | 1,000 watts |
| • Power Supply: | 120 VAC-1Ph-60Hz (20A GFCI) |
| • Refrigeration Unit: | Air Cooled (0.26 HP) R-513A |
| • Refrigeration Heat Load To Room: | 4,500 BTU @ 205 CFM |
| • Approximate Distillation Rate: | 2 GPH |
| • Total Operational Solvent Fill Amount: | 1.5 Gallons |
| • Approximate Shipping Weight: | 325 Pounds Crated |