# GENERAL TECHNICAL SPECIFICATIONS - EQUINOX DEGREASERS

| MODEL NUMBER | DIMENSIONS IN INCHES (APPROX.) | | | | | | | | SOLVENT CAPACITY IN GALLONS | | | | LOAD CAPACITY: POUNDS OF STEEL PER HOUR: PF SOLVENT | ULTRASONICS | DISTILLATION RATE (GPH/PF) | PRIMARY REFRIG. UNIT (HP) (R-448A) | VAPOR TRAP REFRIG. UNIT (HP) (R-448A) | ELECTRIC HEATER (KW) | STANDARD VOLTAGE 60HZ (FLA) | SHIPPING WEIGHT (APPROX.) |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | INSIDE TANK | | | | | OVERALL | | | | | | | | | | | | | | |
| | LENGTH | WIDTH | HEIGHT RINSE SUMP | HEIGHT FREE-BOARD | HEIGHT VAPOR ZONE | WIDTH FT - BK | LENGTH L - R | HEIGHT | BOIL TANK | RINSE TANK | DIST SPRAY TANK | TOTAL | | | | | | | | |
| EQ2 | 10 | 12 | 10 | 20 | 10 | 32" | 68" | 50" | 5.5 | 5.5 | 0.5 | 13 | 50 | N/A | 5 | 1/2 | 1/2 | 2 | 230/1 (21) | 925 |
| EQ2S | | | | | | | | | | | | | | 300 | | | | | 230/1 (29) | 950 |
| EQ3 | 18 | 12 | 12 | 20" | 12 | 58" | 66" | 54" | 16 | 13 | 1.5 | 33 | 300 | N/A | 10 | 2 | 3/4 | 4 | 230/1 (42) | 2200 |
| EQ3S | | | | | | | | | | | | | | 1000 | | | | | 230/1 (50) | 2250 |
| EQ4 | 20 | 14 | 16 | 23 | 16 | 80" | 70" | 65" | 28 | 22 | 2 | 54 | 750 | N/A | 15 | 3 | 1 | 6 | 230/3 (50) | 2450 |
| EQ4S | | | | | | | | | | | | | | 2000 | | | | | 230/3 (66) | 2500 |
| EQ5 | 24 | 20 | 20 | 30 | 20 | 87" | 78" | 80" | 42 | 45 | 3 | 95 | 750 | N/A | 12 | 3 | 2 | 6 | 230/3 (54) | 2850 |
| EQ5S | | | | | | | | | | | | | | 2000 | | | | | 230/3 (70) | 2900 |
| EQ6 | 30 | 24 | 24 | 35 | 24 | 92" | 84" | 93" | 83 | 80 | 5 | 175 | 1200 | N/A | 30 | 7 1/2 | 2 1/2 | 15 | 230/3 (85) | 3250 |
| EQ6S | | | | | | | | | | | | | | 3000 | | | | | 230/3 (115) | 3300 |